

ES-A SERIES

photovoltaic panels

200, 205 & 210 W

evergreensolar®



Made in the USA

MORE electricity

Our ES-A series panels have the best power tolerance in the industry (-0/+5W) and consistently deliver more electricity than competitors in field tests.

GUARANTEED POWER¹

The minimum guaranteed power is the nameplate so you never get less power than you paid for.

INDEPENDENTLY VERIFIED POWER²

Four independent test labs regularly check panel power so you get the power we promise.

ANTI-REFLECTIVE GLASS

Delivering 2–3% more electricity compared to panels with standard glass.

TEMPERATURE RATINGS OVER 90%³

Maintaining up to 4% higher output than most other crystalline silicon panels under hot conditions.

HIGH RANKINGS IN FIELD TESTS⁴

Long-term Photon and TÜV field tests prove Evergreen panels produce more electricity (kWh/kW).

¹ Guaranteed upon initial delivery of the panel to the customer, maximum power up to 4.99 W above nameplate rating; ² Evergreen power testers calibrated by taking the straight average of test data from NREL, TÜV Rheinland PTL, TÜV Rheinland Cologne and Fraunhofer ISE; ³ Based on comparing PTC/STC ratings of major competing multi-crystalline silicon panel brands published by the California Energy Commission in May 2009; ⁴ 2008 Module Tests conducted by Photon and published in Photon International February 2009, TÜV Rheinland tests run from April to September 2008

LESS impact

String Ribbon™ panels have the smallest carbon footprint and fastest energy payback of any silicon-based solar panel ever made.

SMALLEST CARBON FOOTPRINT⁵

Our String Ribbon™ wafers are made with a fraction of the emissions resulting from making conventional silicon panels.

12-MONTH ENERGY PAYBACK⁵

Our panels begin generating truly clean electricity faster than any other silicon-based panel on the market.

100% CARDBOARD FREE REUSABLE PACKAGING

Reduces disposal costs and on-site manpower while eliminating tons of landfill.

LEAD-FREE SOLAR CELLS

Our panels make clean electricity, but the way we make them is clean too.

⁵ Evaluation completed by the Energy Research Foundation of the Netherlands (ECN), May 2009



STRING RIBBON™ SOLAR PANELS OFFERING EXCEPTIONAL PERFORMANCE AND INDUSTRY-LEADING ENVIRONMENTAL CREDENTIALS. IN SHORT, MORE ELECTRICITY AND LESS IMPACT.

All Evergreen panels come with a 5 year workmanship and 25 year limited power warranty. For full details see the **Evergreen Solar Limited Warranty** available upon request or online. This product is certified to UL 1703, UL 4703, UL Fire Safety Class C, IEC 61215 Ed.2, IEC 61730 Class A, FSEC and KTL standards. **String Ribbon** is a trademark of Evergreen Solar, Inc. Evergreen Solar's wafer manufacturing technology is patented in the United States and other countries. Copyright © Evergreen Solar, Inc 2009.



ELECTRICAL characteristics

Standard Test Conditions (STC)¹

	ES-A-200 -fa3*	ES-A-205 -fa3*	ES-A-210 -fa3*	
P_{mp}^2	200	205	210	W
$P_{tolerance}$	-0/+4.99 (-0/+2.5)	-0/+4.99 (-0/+2.5)	-0/+4.99 (-0/+2.5)	W (%)
$P_{mp,max}$	204.99	209.99	214.99	W
$P_{mp,min}$	200.00	205.00	210.00	W
η_{min}	12.7	13.1	13.4	%
V_{mp}	18.1	18.2	18.3	V
I_{mp}	11.05	11.27	11.48	A
V_{oc}	22.6	22.7	22.8	V
I_{sc}	11.80	11.93	12.11	A

Nominal Operating Cell Temperature Conditions (NOCT)³

T_{NOCT}	45.4	45.4	45.4	°C
P_{max}	146.4	150.1	153.8	W
V_{mp}	16.5	16.6	16.7	V
I_{mp}	8.87	9.04	9.21	A
V_{oc}	20.8	21.0	21.1	V
I_{sc}	9.44	9.57	9.76	A

Low Irradiance

The typical relative reduction of module efficiency at an irradiance of 200W/m² both at 25°C cell temperature and spectrum AM 1.5 is 0%.

Temperature Coefficients


γP_{mp}	-0.43	%/°C
βV_{mp}	-0.40	%/°C
αI_{mp}	-0.03	%/°C
βV_{oc}	-0.31	%/°C
αI_{sc}	+0.05	%/°C

System Design

Maximum Reverse Current ⁴	20 A
Maximum DC System Voltage (TÜV)	1000 V
Maximum Combined Wind and Snow Load ⁵	5.4 kPa

¹ 1000 W/m², 25°C cell temperature, AM 1.5 spectrum; ² Maximum power point or rated power; ³ 800 W/m², 20°C ambient temperature, 1 m/s wind speed, AM 1.5 spectrum; ⁴ Also known as Series Fuse Rating; ⁵ When the panel is mounted using Mounting Method A (offset mounting) with rails 330mm (+/-20mm) from each short side of the panel as described in the Mounting Guide for this product; * F-framed, a-low voltage, 3-matt blue (textured) cells and black anodized frame

MECHANICAL specifications



The above drawing is a graphical representation of the product; for engineering quality drawings please contact Evergreen Solar. MC® is a registered trademark of Multi-Contact AG. Product constructed with 114 multi-crystalline silicon String Ribbon™ solar cells, anti-reflective tempered solar glass, EVA encapsulant, polymer back-skin and a black anodized double-walled aluminum frame.

Product packaged 28 per pallet and tested to International Safe Transit Association (ISTA) Standard 2B. All specifications in this product information sheet conform to EN 50380. See the [Evergreen Solar Safety, Installation and Operation Manual](#), [Mounting Guide](#) and [Inverter Selection Guide](#) for further information on approved installation and use of this product.

Due to continuous innovation, research and product improvement, the specifications in this product information sheet are subject to change without notice. No rights can be derived from this product information sheet and Evergreen Solar assumes no liability whatsoever connected to or resulting from the use of any information contained herein.

PARTNER



Evergreen Solar Inc.
www.evergreensolar.com

WORLDWIDE HEADQUARTERS

Evergreen Solar Inc.
138 Bartlett Street, Marlboro, MA 01752, USA
T +1.508.357.2221 F +1.508.229.0747
info@evergreensolar.com

CUSTOMER SERVICE Americas and Asia

Evergreen Solar Inc.
138 Bartlett Street, Marlboro, MA 01752, USA
T +1.508.357.2221 F +1.508.229.0747
sales@evergreensolar.com

ES-A_200_205_210_fa3_EN_K_010609; effective June 1st 2009